

# WHEELED CONE PLANT WC1000/WC1000LS



## Standard Supply

- ▶ Cone crusher Model TC1000 with squirrel cage electric motor of 170 kW.
- ▶ Chassis walkway assembly with ladder.
- ▶ Walkway platforms around the screen (LH, RH and rear side).
- ▶ Cone crusher lubrication tank, hydraulic tank and cooler with accessories.
- ▶ Automation - system 2 PLC control for crusher management.
- ▶ Terex 4 deck vibrating screen 5' x 14' with 15 kW motor and 5' X 18' with 22 kW motor.
- ▶ Jacks with handles - 2 nos.
- ▶ Emergency stops - 4 nos.
- ▶ Mounted on chassis with removable type double axle bogie with tail lights.
- ▶ All electric plant.

## Electricals

- ▶ Cone unit electricals including cable kit, control panel and operator panel (standard plant set for 415V/50Hz) weather protected, robust control panel houses user-friendly controls

## Options

- ▶ **SURGE HOPPER**  
16 cub mt chassis mounted surge hopper with pan feeder (2500 mm x 800 mm with 2 x 1.5 kW motors)
- ▶ **CRUSHER CHAMBER CONFIGURATIONS**  
Extra Coarse - max feed size 195 mm  
Medium Coarse - max feed size 160 mm  
Autosand - max feed size 63 mm

# SPECIFICATIONS

# Terex® Minerals Processing Systems WC1000/ WC1000LS

## TRANSPORT MODE

	WC1000	WC1000LS
Overall Width	3398mm	3399mm
Overall Height	4743mm	4734mm
Overall Length	13966mm	14680mm

## OPERATING MODE

	WC1000	WC1000LS
Overall Width	4949mm	4992mm
Overall Height	7266mm	7914mm
Overall Length	12200mm	13394mm

Max Feed Size	195 mm
<b>Capacity Range</b>	
Extra Coarse	125 MtpH - 190 MtpH
Medium Coarse	140 MtpH - 220 MtpH
Autosand	85 MtpH - 150 MtpH
Total Connected Load	193.5 kW
<b>Weights</b>	
Chassis (complete with crusher and screen)	35 tons
Crusher TC1000	10 tons

\* The capacity are based on dry, free flowing material with a Crushing Work Index of 16 and a bulk density of 1600 kg/cu m (100 lbs/cu ft).  
The data requires careful interpretation for particular materials and applications as machine capacity can be greatly affected by material properties and method of feeding.

### Local Contact:

[www.terexmps.com](http://www.terexmps.com)

Effective Date: February 2014. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and Terex makes no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation and/or its subsidiaries in the USA and other countries. All rights are reserved. Terex is a registered trademark of Terex Corporation in the USA and many other countries. © 2014 Terex Corporation.

Terex® Minerals Processing Systems  
Form 25992 A4 (2/14)

Europe, Russia, Africa +44 (0) 28 82 418 790 • Turkey, Middle East, Northern Africa +90 312 354 90 90 • India +91 4344 302 000  
Malaysia +60 3 5631 6199 • Thailand +66 2 316 4656 • Australia +61 3 8551 9300 • North America +1 800 248 3821  
Latin and South America +1 989 288 3121



**WORKS FOR YOU.™**